

Thermal Conductivity and Laser Deposition Models: August 2026 upgrades

August 27, 2026

Contents

1	General Hydrodynamic Equations	2
2	Classical Laser Deposition Model	3
3	Classical Conductivity Model	4
3.1	Electron-Ion Coupling Coefficient	8
4	Conductivity Model and Benchmarks for Plasmas with Degenerate Electrons	8
5	Short-Pulse Laser Deposition Model and Benchmarks	10
5.1	Uniform-slab limit: analytic Fresnel absorption	14
5.2	Laser absorption for different polarization	17
5.3	Deposition profile verification	17
5.4	Laser absorption as a function of wavelength	18
5.5	Laser absorption comparison with experiment	21
5.6	Benchmark for an Integrated Simulation	23
6	Supplementary Materials	26

1 General Hydrodynamic Equations

HELIOS-CR is a 1-D radiation-magnetohydrodynamics code that is used to simulate the dynamic evolution of plasmas created in high-energy-density physics (HEDP) experiments [1]. *HELIOS-CR* solves Lagrangian hydrodynamics equations for plasmas in planar, cylindrical, and spherical geometries. Plasmas may be composed of a single material or multiple layers (or regions) of materials. While radiation-hydrodynamics codes typically rely on equation of state and opacity databases that are generated under the assumption of local thermodynamic equilibrium (LTE), *HELIOS-CR* provides the added capability to simulate the non-LTE kinetics of plasmas by solving multi-level atomic rate equations at each time step in the simulation. This can be particularly important when modeling experiments in which deviations from LTE can significantly affect the overall energetics of the plasma, such as when radiation energy losses represent a significant fraction of the overall energy budget.

HELIOS-CR solves the equation of motion for a single fluid. Electrons and ions are assumed to be co-moving. Pressure contributions to the equation of motion come from electrons, ions, radiation, and the magnetic field. Energy transport in the plasma can be treated using either a one-temperature ($T_e = T_i$) or two-temperature ($T_e \neq T_i$) model. Both the electrons and ions are assumed to have Maxwellian distributions defined by their respective temperatures T_e and T_i .

In Lagrangian hydrodynamics, the spatial grid moves with the fluid. No mass crosses volume element boundaries. It is useful to express the spatial coordinate in terms of the independent Lagrangian mass variable:

$$dm_0 = \rho(r) r^{\delta-1} dr, \quad (1)$$

where ρ is the mass density, r is the spatial position (i.e., the radius in cylindrical and spherical geometries), and $\delta = 1, 2$, or 3 for planar, cylindrical, or spherical geometry, respectively. In this system, the continuity (mass conservation) equation is automatically satisfied.

The momentum conservation equation is solved in the one-fluid approximation, where the plasma electrons and ions are assumed to flow together as a single fluid. The momentum conservation equation is given by:

$$\frac{\partial u}{\partial t} = -r^{\delta-1} \frac{\partial}{\partial m_0} (P + q) - \frac{1}{8\pi r} \frac{\partial}{\partial m_0} (r^2 B^2), \quad (2)$$

where u is the fluid velocity, t is the time, P is the total pressure due to electrons, ions, and radiation, q is the von Neumann artificial viscosity, and B is the magnetic field induced by the axial current (non-zero for cylindrical geometry only). The artificial viscosity, which is included in the equation of motion to handle shocks, effectively smooths the shock over a small number of zones.

The conservation-of-energy equations are written in terms of temperature diffusion equations for the electrons and ions, and are given by:

$$C_{v,e} \frac{\partial T_e}{\partial t} = \frac{\partial}{\partial m_0} \left(r^{\delta-1} K_e \frac{\partial T_e}{\partial r} \right) - \omega_{ei} (T_e - T_i) - \left[\frac{\partial E_e}{\partial V} + P_e \right] \frac{\partial V}{\partial t} T_e + R_{Abs} - R_{Emis} + \Psi + S_e, \quad (3)$$

and

$$C_{v,i} \frac{\partial T_i}{\partial t} = \frac{\partial}{\partial m_0} \left(r^{\delta-1} K_i \frac{\partial T_i}{\partial r} \right) + \omega_{ei} (T_e - T_i) - \left[\frac{\partial E_i}{\partial V} + P_i \right] \frac{\partial V}{\partial t} T_i - q \frac{\partial V}{\partial t}, \quad (4)$$

where $C_{v,e}$ ($C_{v,i}$) is the electron (ion) specific heat, K_e (K_i) is the electron (ion) thermal conductivity, E_e (E_i) is the electron (ion) specific internal energy, ω_{ei} is the electron-ion collisional coupling term, S_e is the source term due to laser or external electron/ion beam energy deposition, Ψ is the joule heating term (for MHD option), and R_{Abs} and R_{Emis} are the radiation absorption and emission terms.

2 Classical Laser Deposition Model

The existing laser deposition model in *HELIOS-CR* utilizes ray tracing algorithms for spherical, cylindrical, and planar geometries. It is assumed that laser light propagates through the plasma instantaneously. Effects due to the polarization of laser light are currently neglected. User input to *HELIOS-CR* includes the laser wavelength (λ_L), the time-dependent incident laser power ($P_L(t)$), and the boundary at which the incident laser source originates. Laser energy is deposited in the plasma using an inverse Bremsstrahlung model when the electron density is less than the critical density. For laser light with a wavelength λ_L , the critical density is given by [2]:

$$n_{e,crit} = \frac{\varepsilon_0 m_e}{e^2} \omega_L^2 = (1.11 \times 10^{21} \text{ cm}^{-3}) \lambda_{L,\mu\text{m}}^{-2}, \quad (5)$$

where ε_0 is the permittivity in free space, $\omega_L = 2\pi c/\lambda_L$ is the angular frequency of the laser light, c is the speed of light, $\lambda_{L,\mu\text{m}}$ is the laser wavelength in nm, and m_e and e are the electron mass and charge, respectively. Laser energy is not allowed to penetrate beyond the critical surface. The depth at which the laser light penetrates is determined from the absorption coefficient [3]:

$$\kappa = (2\pi)^{1/2} \left(\frac{16\pi}{3} \right) \frac{e^6}{c(m_e k T_e)^{3/2}} Z n_e^2 \frac{\ln \Lambda_{ei}}{\omega_L^2 \sqrt{1 - (\omega_P/\omega_L)^2}}, \quad (6)$$

where k is Boltzmann's constant, n_e is the electron density, T_e is the electron temperature, Z is the mean charge of the plasma, $\omega_P = (4\pi e^2 n_e / m_e)^{1/2}$ is the plasma frequency, and $\ln \Lambda_{ei}$ is the electron-ion Coulomb logarithm.

In planar geometry, the laser deposition source term S_e is computed by solving an integral form of the radiative transfer equation along a single ray which has an angle of incidence θ with respect to the surface normal. In spherical and cylindrical geometries, the beam is modeled with multiple rays contained within a cone of half-angle α converging to a point F located at a distance d from the origin (see Figure 1(a)). Each ray within the cone has a power such that the beam intensity is uniform throughout the cone. In addition, each ray is allowed to refract (i.e., change angles) as it propagates through the plasma. The refraction is computed using a geometrical optics model with the plasma refractive index being governed by local values of electron density. Figure 1(b) shows an example of rays propagating through a spherical plasma. In *HELIOS-CR* v.12.0.0 (August 2026 release), an option to visualize ray tracing has been implemented (for spherical geometry only). The




Figure 1: Schematic illustrations showing: (a) laser beam cone and target geometry for spherical plasma simulation, and (b) example of refraction of laser beam rays for a spherical target.

color of each line segment indicates the remaining power in each ray. The total source term is obtained by summing over all rays. *HELIOS-CR* also supports non-zero laser spot size at the focal point with either uniform or Gaussian distribution of laser power. The power in each ray for ray tracing is adjusted according to the specified distribution.

HELIOS-CR also has an option to include the effect of laser absorption on atomic bound-bound and bound-free transitions based on the information contained in opacity databases. Users can also specify a fraction of the laser energy that can be reflected off the critical surface.

3 Classical Conductivity Model

The conduction coefficients are the classical, Spitzer values of thermal conductivity and electron-ion coupling [4]. The electron thermal conductivity in Equation 3 is given by:

$$K_e = 20 \left(\frac{2}{\pi} \right)^{3/2} \frac{(k_B T_e)^{5/2} k_B \varepsilon \delta_T}{m_e^{1/2} e^4 Z \ln \Lambda_{ei}}, \quad (7)$$

where the correction for the ionization stage of the plasma is defined as:

$$\varepsilon \delta_T(Z) = \frac{0.43 Z}{(3.44 + Z + 0.26 \ln Z)}. \quad (8)$$

This correction is important for accurate calculation of conductivities, especially for weakly-ionized plasmas where the function varies rapidly with Z . The implementation of this correction differs across hydro codes:

FLASH [5]:
$$\varepsilon \delta_T(Z) = \left(\frac{8}{\pi} \right)^{3/2} \frac{1}{Z \left(1 + \frac{3.3}{Z} \right)},$$

$$\begin{aligned}
\text{MULTI- FS [6]:} \quad \varepsilon\delta_T(Z) &= \frac{3}{4\sqrt{2\pi}} \cdot \frac{3.22(Z + 0.24)}{Z(1 + 0.24Z)}, \\
\text{HYADES Equ. 3 [7]:} \quad \varepsilon\delta_T(Z) &= \frac{3}{4\sqrt{2\pi}} \cdot \frac{\gamma_0}{\delta_0 Z}, \\
\text{HYADES Equ. for } \varepsilon\delta: \quad \varepsilon\delta_T(Z) &= 20 \left(\frac{2}{\pi}\right)^{3/2} \frac{15\pi}{256} \frac{z(433z + 45)}{z(217z + 151) + 9}.
\end{aligned}$$

We have found, however, that the functional dependence on Z is similar for all approximations (Figure 2) and does not significantly alter the conductivity values.




Figure 2: Mean ion charge correction for electron conductivity.

There are various approximations for the electron-ion Coulomb logarithm ($\ln \Lambda_{ei}$). The default model implemented in *HELIOS-CR* v.12.0.0 (August 2026 release) is computed based on a combination of formalisms by Skupsky [8] at low electron energies and by Mehlhorn [9] at high energies.

The ion thermal conductivity in Equation 4 is given by:

$$K_i = 20 \left(\frac{2}{\pi}\right)^{3/2} \frac{(k_B T_i)^{5/2} k_B}{m_i^{1/2} e^4 Z^4 \ln \Lambda_{ii}}, \quad (9)$$

where

$$\ln \Lambda_{ii} = \max \left\{ 5, 24 - \ln \left(\frac{\sqrt{2n_i} Z^3}{T_i^{3/2}} \right) \right\}.$$

Spitzer conductivities are expected to be accurate at high temperatures. Plotted in Figure 3 are temperature-dependent conductivities for Al near solid density computed with Spitzer, using SESAME tables [10], and the Lee-More model [11]. The differences between the models for the temperatures below 10 eV are substantial. Additional conductivity benchmarks can be found in section 6 of this report.




Figure 3: Temperature-dependent conductivities for Al near solid density computed with different models.

In finite-difference form, the thermal conductivities must be evaluated on the zone boundaries; hence averaged quantities from the adjacent zone centers must be used. This average is taken using the zone width weighted harmonic mean:

$$K_e = \frac{\Delta r_j^+ + \Delta r_j^-}{\frac{\Delta r_j^+}{K_{ej}^+} + \frac{\Delta r_j^-}{K_{ej}^-}}, \quad (10)$$

where

$$\Delta r_j^+ = r_{j+1} - r_j \quad (11)$$

$$\Delta r_j^- = r_j - r_{j-1} \quad (12)$$

$$K_{ej}^+ = \frac{Const_e T_{ej}^2 T_{ej+1/2}^{1/2}}{\varepsilon \delta_T(Z_{j+1/2}) (\ln \Lambda_{ei})_{j+1/2}}$$

$$K_{ej}^- = \frac{Const_e T_{ej}^2 T_{ej-1/2}^{1/2}}{\varepsilon \delta_T(Z_{j-1/2}) (\ln \Lambda_{ei})_{j-1/2}}. \quad (13)$$

A similar expression is used for the ions, with

$$K_i^+ = \frac{Const_i T_{i_j}^2 T_{i_{j+1/2}}^{1/2}}{(A_{j+1/2})^{1/2} (Z_{j+1/2})^4 (\ln \Lambda_{ii})_{j+1/2}}$$

$$K_i^- = \frac{Const_i T_{i_j}^2 T_{i_{j-1/2}}^{1/2}}{(A_{j-1/2})^{1/2} (Z_{j-1/2})^4 (\ln \Lambda_{ii})_{j-1/2}}, \quad (14)$$

where $Const_e$ and $Const_i$ correspond to appropriate numerical factors. These expressions will most heavily weight the lowest conductivity in the zones centered at $j + 1/2$ or $j - 1/2$. Several benchmark simulations and comparisons against analytic solutions are presented in section 6 of this report.

In the presence of strong thermal gradients, that is, large fluxes, the diffusion approximation can break down and predict unphysically large thermal fluxes. To adjust for this, the electron thermal conduction is augmented with a flux limiter. This maximum permissible flux is defined classically (see, for example, [5]):

$$q_{\max} = C_{FL} n_e k_B T_e \left(\frac{k_B T_e}{m_e} \right)^{1/2}, \quad (15)$$

where C_{FL} is a user-specified multiplicative constant. The typical value for this constant is 0.06. In finite difference form, this is expressed as

$$q_{\max_j}^{n+1/2} = C_{FL} m_e^{-1/2} (n_{e_{j-1/2}}^{n+1/2} + n_{e_{j+1/2}}^{n+1/2}) T_{e_j}^{n+1/2} \left[(T_{e_{j-1/2}}^{n+1/2})^{1/2} + (T_{e_{j+1/2}}^{n+1/2})^{1/2} \right]. \quad (16)$$

Note that this quantity is evaluated on a zone boundary. The flux limit is implemented by redefining the matrix elements in the system of equations for the electron temperatures as

$$\frac{(r_j^{n+1/2})^{\delta-1}}{\frac{\Delta r_{j+1/2}}{K_{e_j}^+} + \frac{\Delta r_{j-1/2}}{K_{e_j}^-} + \frac{|T_{e_{j+1/2}}^{n+1/2} - T_{e_{j-1/2}}^{n+1/2}|}{q_{\max_j}}} \text{ (harmonic),} \quad (17)$$

$$\frac{(r_j^{n+1/2})^{\delta-1}}{\left[\left(\frac{\Delta r_{j+1/2}}{K_{e_j}^+} + \frac{\Delta r_{j-1/2}}{K_{e_j}^-} \right)^2 + \left(\frac{|T_{e_{j+1/2}}^{n+1/2} - T_{e_{j-1/2}}^{n+1/2}|}{q_{\max_j}} \right)^2 \right]^{1/2}} \text{ (Larsen), or} \quad (18)$$

$$(r_j^{n+1/2})^{\delta-1} \min \left[\left(\frac{\Delta r_{j+1/2}}{K_{e_j}^+} + \frac{\Delta r_{j-1/2}}{K_{e_j}^-} \right)^{-1}, \frac{q_{\max_j}}{|T_{e_{j+1/2}}^{n+1/2} - T_{e_{j-1/2}}^{n+1/2}|} \right] \text{ (min/max).} \quad (19)$$

Options for Larsen and min/max limiters have been implemented in *HELIOS-CR* v.12.0.0 (August 2026 release).

3.1 Electron-Ion Coupling Coefficient

The electron and ion temperatures are coupled by the expression

$$\frac{\partial T_e}{\partial t} = \frac{T_i - T_e}{t_{ei}}, \quad (20)$$

where t_{ei} is the characteristic electron-ion collision time. In terms of the electron and ion diffusion equations, this expression becomes

$$C_{v_e} \frac{\partial T_e}{\partial t} = \dots + \frac{C_{v_e}}{t_{ei}} (T_i - T_e) + \dots$$

hence, the definition of the coupling coefficient in Equations 3 and 4 is

$$\omega_c = \frac{C_{v_e}}{t_{ei}} = C_{v_e} \nu_{ei} \quad (21)$$

where the electron-ion collision frequency is defined in the classical Spitzer form:

$$\nu_e = \frac{4\sqrt{2}\pi \ln \Lambda e^4 Z n_e}{3\sqrt{m_e} (kT_e)^{3/2}}. \quad (22)$$

The same expression for the collision frequency is used in Equation 7 for the thermal conductivity.

4 Conductivity Model and Benchmarks for Plasmas with Degenerate Electrons

For high-temperature, weakly coupled plasmas, a well-established classical theory for the electron-ion collision frequency ν_{ei} exists. *HELIOS-CR* currently utilizes a simple parametric formalism that describes $\nu_{Sp} \equiv \nu_{ei}$ in terms of plasma temperature, average ionization, and other plasma properties according to Equation 22.

This approach, however, may not be adequate for warm dense matter (WDM) and metal-like solids, when electrons become degenerate. Additional complications arise due to the effect of bound electrons and strong ion-ion correlations. In metals, the electron collision frequency is known to scale linearly with electron temperature, not as $T_e^{-3/2}$ as prescribed by the classical theory. At low temperature, metal electrons scatter due to electron-phonon interactions, and the basic parametric structure of the collision frequency is obtained as:

$$\nu_{ep} = K_{wdm} \frac{e^2}{\hbar v_F} \frac{kT_i}{\hbar}, \quad (23)$$

where T_i is the ion temperature describing phonons, $v_F = (3\pi^2 n_e)^{1/3} \hbar / m_e$ is the characteristic Fermi velocity of the degenerate electron gas, and K_{wdm} is a semi-empirical factor absorbing the coupling strength and effective-mass effects omitted by the free-electron estimate. **It should be calibrated to a measured quantity:** e.g., for aluminium, the room-temperature value inferred from the measured reflectivity at 400 nm, $\nu_{Al} \simeq 8.5e14 s^{-1}$,

requires $K_{wds} \approx 18.8$. The collision frequency can be normalized independently for the three channels—the laser deposition (via the dielectric function), the electrical and thermal conductivity, and the electron–ion heat exchange. Each normalization should therefore be adjusted to the corresponding measured quantity—the laser reflectivity, the conductivity, and the electron–ion energy exchange—for the particular metal and temperature range of interest.

To make the transition from the WDM regime to the high-temperature Spitzer regime, the two forms are combined by a harmonic interpolation and capped at the Ioffe–Regel ceiling,

$$\nu_{EP} = \min \left[\left(\nu_{wdm}^{-1} + \nu_{Sp}^{-1} \right)^{-1}, \frac{v_e}{R_0} \right], \quad (24)$$

where $v_e = \sqrt{v_F^2 + v_{th}^2}$ and $R_0 = \left(\frac{3}{4\pi n_i} \right)^{1/3}$.

The ceiling reflects that the mean free path $\ell = v_e/\nu$ cannot fall below the interatomic spacing R_0 : once $\ell \sim R_0$, the electron scatters before completing a single oscillation and the quasiparticle picture breaks down (resistivity saturation). Because $v_e = \sqrt{v_F^2 + v_{th}^2}$, the ceiling is flat at v_F/R_0 in the degenerate regime ($T_e \lesssim T_F$) and rises as $\sqrt{T_e}$ once thermal motion dominates.

A different approach based on the Drude-Sommerfeld model has also been implemented. It attributes the dominant part of the collision frequency to electron–ion collisions, just as in the case of a classical plasma, but now taking into account electron degeneracy in warm dense matter and modifications in Coulomb scattering which apply to slow electrons. With this approach, the dynamical collision frequency is well suited for laser absorption and has appropriate dependence on the electron temperature and laser frequency. In the limit $mv_{th}^3/(Ze^2\omega_L) < 1$, the collision frequency can be expressed as:

$$\nu_{wdm} = \frac{4\pi^2 e^{2/3} \Gamma(1/3)}{15 \cdot 3^{5/6} \Gamma(2/3)} \frac{Ze^4 n_e}{m_e^2 v_{th}^2} \left(\frac{m_e v_{th}^3}{Ze^2 \tilde{\omega}} \right) \left\langle \frac{v_{th}}{v} \right\rangle, \quad (25)$$

where $\tilde{\omega} = \max(\omega_L, \omega_P)$. Averaging the velocities over the Fermi distribution function $f(\epsilon) = 1 + e^{(\epsilon - \mu)/kT_e}$, including Pauli blocking, gives:

$$\left\langle \frac{v_{th}}{v} \right\rangle = \frac{3v_{th}}{mv_F^3} \int_0^\infty f(\epsilon) (1 - f(\epsilon + \hbar\omega_L)) d\epsilon = 3 \left(\frac{v_{th}}{v} \right)^3 \ln \left(\frac{1 + e^y}{1 + e^{y-z}} \right) (1 - e^{-z})^{-1}, \quad (26)$$

where we introduce variables y and z that represent μ/kT_e and $\hbar\omega_L/kT_e$ respectively, and μ is the chemical potential that can be estimated to a good precision with simple parametric formulas, e.g. Equation 10.35 in [12].

A smooth transition between the WDM and Spitzer regime can be expressed in this form:

$$\nu_{DS}(T_e, \omega_L) \simeq 2\sqrt{2\pi} \frac{Ze^4 n_e}{m_e^{1/2} (kT_e)^{3/2}} \ln \left[1 + K_{ds} \frac{1.32}{\sqrt{2\pi}} \frac{kT_e}{m_e^{1/3} (Ze^2 \tilde{\omega})^{2/3}} \right] F(T_e, \hbar\omega_L), \quad (27)$$

with the Fermi factor having appropriate asymptotic behavior:

$$F(T_e, \hbar\omega_L) = \sqrt{\pi/2} \langle v_{th}/v \rangle \rightarrow \begin{cases} 3/4 \sqrt{\pi/2} v_{th}/v_F \min(\hbar T_F, 1) & T_e \rightarrow 0, \\ 1 & T_e \rightarrow \infty, \end{cases}, \quad (28)$$

where the free parameter K_{ds} has a default value of 1, but can be adjusted.

The three models for electron-ion collision frequency calculation have been implemented in *HELIOS-CR* by Equations 22, 24, and 27. They are referred to as Classical, Electron-phonon, and Drude-Sommerfeld, respectively. Classical and Electron-phonon models are enabled as options for electron thermal conductivity ($K_e \nu_{ei}^{-1}$ and the electron-ion coupling coefficient (Equation 21). Drude-Sommerfeld has an explicit dependency on the laser frequency and is only available for the laser deposition model, as discussed in Section 5. For each spatial region in *HELIOS-CR*, the model choice for conductivities can be specified independently. In the case of the electron-phonon model, the values for K_{wdm} are required as input. The default values for K_{wdm} are the ones given in [6], and it is up to the user to determine these empirical factors for other regimes, most likely by comparing with experimental results. The differencing scheme for conductivity is slightly modified compared to Equation 13 to be consistent with [6]. From cell-centered conduction values K_j^{cell} , the zone-boundary conduction values K_j^{int} can be determined as follows:

$$K_j^{int} = \frac{K_j^{cell}/T_{e,j}^{3/2} + K_{j-1}^{cell}/T_{e,j-1}^{3/2}}{2} \times \frac{T_{e,j}^{3/2} + T_{e,j-1}^{3/2}}{2}. \quad (29)$$

Regardless of the choice for the collision frequency, the flux limiters are implemented according to Equations 17, 18, or 19.

Figure 4 compares the collision frequencies obtained from the *HELIOS-CR* simulations with these models as a function of the electron temperature. The collision frequency has the correct three-regime shape—a linear increase with the temperature, a degenerate electron-phonon plateau bounded by the ceiling, and a Spitzer decline. The empirical constant K_{ds} affects mostly the low-temperature ($T_e \lesssim 10eV$) branch: the larger the constant, the higher the collision frequency. Above $\sim 800eV$ the simulation results agree across the different models except the Drude-Sommerfeld model. The Drude-Sommerfeld model gives significantly lower values across the whole range below $\sim 1keV$ before merging with the Spitzer branch.

5 Short-Pulse Laser Deposition Model and Benchmarks

Although the deposition models in *HELIOS-CR* have been extensively tested for simulations that include longer nanosecond-scale laser pulses, they may not be adequate for ultra-short pulses. Therefore, we have developed a new model for the laser energy deposition suitable for sub-picosecond laser pulses with intensities up to $10^{17} W/cm^2$. In this new development, Prism has closely followed the formalism implemented in the MULTI-fs code [6, 13].

Due to ultra-short interaction times, the laser-matter interaction occurs on very steep fronts. If the plasma scale length is comparable to the laser wavelength, a full solution of Maxwell's equations has been implemented. In the quasi-stationary approximation, propagation of an electromagnetic wave with frequency ω_L in the plasma with complex dielectric constant ϵ can be described by the following equations:




Figure 4: Collision frequency versus electron temperature for aluminium at solid density. The electron–phonon branches (for several K_{wds}) rise linearly with T_i , the Drude–Sommerfeld model lies below and merges with the Spitzer branch at high temperature, and the Ioffe–Regel ceiling v_e/R_0 (dotted) caps the collision frequency. The Fermi temperature T_F marks the degenerate–classical boundary.

$$\frac{dV(r)}{dr} = ip\beta U, \quad \frac{dU(r)}{dr} = i\frac{\beta}{p}V, \quad (30)$$

where functions $U(r)$ and $V(r)$ represent the complex amplitudes of the oscillatory electric and magnetic fields at the position r . For s-polarized light, $p = \sqrt{\epsilon - \alpha^2}$ and $\beta = \omega_L p/c$. For p-polarized light, $p = \sqrt{\epsilon - \alpha^2}/\epsilon$ and $\beta = \omega_L p\epsilon/c$. Parameter α is defined as $k_\perp c/\omega_L$ with the transversal component $k_\perp$ of the wavenumber k .

Let us consider a material layer located between positions r_1 and r_{N+1} with the laser propagating from the left from a vacuum region. In vacuum, $\epsilon = 1$ and α reduces to $\sin\theta$, where θ is the angle of incidence of the laser light into the region. Therefore, outside of the material layer, $p = \cos\theta$ and the amplitudes of waves propagating in the positive and negative direction are $C_\pm = \frac{1}{2}(U \pm V/\cos\theta)$. With the laser intensity defined as I_L , the boundary conditions for C at positions r_1 and r_{N+1} become:

$$\sqrt{\frac{8\pi I_L}{c}} = C_+|_{r=r_1} = \frac{1}{2}\left(U_1 + \frac{V_1}{\cos\theta}\right) \quad \text{and} \quad 0 = C_-|_{r=r_{N+1}} = \frac{1}{2}\left(U_{N+1} + \frac{V_{N+1}}{\cos\theta}\right). \quad (31)$$

In order to solve for $U(r)$ and $V(r)$, equation 30, subject to boundary conditions 31, needs to be integrated.

In the material, the complex dielectric constant is evaluated from local zone-centered material properties:

$$\hat{\epsilon} = 1 - \frac{\omega_P^2}{\omega^2(1 + i\nu_e/\omega)}, \quad (32)$$

$\omega_p^2 = 4\pi e^2 n_e/m_e$ is the plasma frequency and ω is the laser frequency.

The wave equation for the laser fields U or V propagating through the plasma follows from the Maxwell equations and takes the Helmholtz form

$$\frac{d^2(U/V)}{dr^2} + \frac{\omega^2}{c^2} \hat{\epsilon}(\omega) (U/V) = 0, \quad (33)$$

so the dielectric function $\hat{\epsilon}$ sets the spatial behaviour of the field: where $\text{Re } \hat{\epsilon} > 0$ the wave propagates, and beyond the critical surface ($\text{Re } \hat{\epsilon} < 0$, i.e. $n_e > n_c$) it becomes evanescent. For a slowly varying density profile, the solution of the wave equation (the WKB limit of the Helmholtz equation) is

$$(U/V)(r) \sim \exp\left(i \frac{\omega}{c} \int^r \sqrt{\hat{\epsilon}(\omega)} dr'\right), \quad (34)$$

so the dielectric function directly sets the propagation and damping of the field: the real part of $\sqrt{\hat{\epsilon}}$ gives the phase, and its imaginary part—carried by the collision frequency ν_{ei} through Eq. (32)—attenuates the wave and produces absorption.

The material properties are assumed to be constant within each hydro cell j ; therefore, at a boundary between cells j and $j+1$, equation 30 can be solved analytically to find the field values:

$$\begin{bmatrix} U_j \\ V_j \end{bmatrix} = \begin{bmatrix} \cos(\beta_j \Delta r_j) & -\frac{i}{p_j} \sin(\beta_j \Delta r_j) \\ -ip_j \sin(\beta_j \Delta r_j) & \cos(\beta_j \Delta r_j) \end{bmatrix} \begin{bmatrix} U_{j+1} \\ V_{j+1} \end{bmatrix}. \quad (35)$$

Using boundary conditions 31, one can determine the values of U and V at the interface $N + 1$, and system 35 can be solved recursively to obtain U and V on all cell boundaries. The net laser energy flux can then be computed as follows:

$$\phi_j = \frac{c}{16\pi} (U_j V_j^* + V_j U_j^*). \quad (36)$$

The value $I_L \cos \theta - \phi_1$ at the material interface 1 represents the power flux reflected by the region, while ϕ_{N+1} represents the power flux transmitted by the region.

The laser deposition source term S_e in the discretized form of the electron energy equation 3 can be easily expressed through the differences of the net fluxes across the cell boundaries.

$$S_{e,j} \sim \frac{\phi_j - \phi_{j+1}}{m_j}. \quad (37)$$

To validate the implementation of the wave-solver algorithm, the comparisons described below have been performed. The *HELIOS-CR* results correspond to the first computational cycle—the stage at which the plasma parameters have not yet been affected by the laser propagation. The effective charge Z_{eff} and the ion density are taken directly from the code and substituted into the analytic expressions, so that any discrepancy arising from the equation-of-state data is eliminated.

The general solution to Eq. 30 is:

$$\begin{aligned} U(r) &= C_+ e^{i\beta r} + C_- e^{-i\beta r}, \\ V(r) &= p(C_+ e^{i\beta r} - C_- e^{-i\beta r}). \end{aligned} \quad (38)$$

For the case of constant plasma conditions, the plasma can be treated as a single cell, and the boundary conditions in Eq. 31 reduce to:

$$\sqrt{\frac{8\pi I_L}{c}} = \frac{1}{2} (U(0) + V(0)) \quad \text{and} \quad 0 = U(R) + V(R). \quad (39)$$

where R is the maximum plasma node position, and the angle of incidence θ is zero (normal incidence). Applying these boundary conditions, Eq. 38 becomes a system of equations which can be solved for C_+ and C_- . Since β and p are determined by plasma conditions (including ν_e), this determines U and V exactly, and the laser deposition can be calculated by Eq. 37. The calculated laser power deposited is compared between the analytic solution, *HELIOS-CR*, and MULTI-fs in Figure 5 for the first simulation cycle of an aluminum plasma, at solid density and room temperature, with a 500 TW/cm² laser at 400 nm for both the Drude-Sommerfeld and Electron-phonon ν_e models. *HELIOS-CR* agrees very well with MULTI-fs and with the analytic solution. In these comparisons, *HELIOS-CR* and MULTI-fs are run with 300 zones. MULTI-fs and *HELIOS-CR* are both run with constant zoning. For the analytic solution, the values for β and p are taken from the *HELIOS-CR* calculation.




Figure 5: Deposition of a 500 TW/cm², 400-nm laser compared between *HELIOS-CR*, MULTI-fs, and the analytic solution for constant plasma conditions for a room-temperature aluminum plasma at solid density, for both the Electron-phonon and Drude-Sommerfeld ν_e models.

This means that the comparison with the analytic solution is a test of the laser deposition algorithm, while the comparison with MULTI-fs is a test of both the laser deposition algorithm and the ν_e calculation for both models.

5.1 Uniform-slab limit: analytic Fresnel absorption

For a uniform slab of constant density and temperature, the absorption follows from the same Fresnel result at the vacuum-plasma interface,

$$A = 1 - R, \quad R = \left| \frac{1 - \hat{N}}{1 + \hat{N}} \right|^2, \quad \hat{N} = \sqrt{\hat{\epsilon}} = \sqrt{1 - \frac{\omega_p^2}{\omega(\omega + i\nu)}}, \quad (40)$$

evaluated with the electron density, temperature, and collision frequency held constant across the slab.

For aluminium at solid density and 800 nm, with $T_e = 30$ eV and the Drude-Sommerfeld

collision frequency $\nu_{DS} \simeq 4.36 \times 10^{15} \text{ s}^{-1}$ ($\nu/\omega \simeq 1.85$), the dielectric function is

$$\hat{\epsilon} = 1 - \frac{\omega_p^2}{\omega(\omega + i\nu)} \simeq -22.4 + 43.4i, \quad \hat{N} = \sqrt{\hat{\epsilon}} \simeq 3.63 + 5.97i, \quad (41)$$

so that

$$R = \left| \frac{1 - \hat{N}}{1 + \hat{N}} \right|^2 \simeq 0.746, \quad A = 1 - R \simeq 0.254 \text{ (25.4\%)}. \quad (42)$$

The large negative $\text{Re } \hat{\epsilon}$ confirms that the wave is evanescent in the target (a skin layer of depth $\delta = c/(\omega \text{Im } \hat{N}) \simeq 21 \text{ nm}$), while the finite $\text{Im } \hat{\epsilon}$ —carried by the collision frequency ν —produces the 25.4% absorption.

Figure 6 (a) shows the analytical absorption over temperature for all four collision models. The Drude–Sommerfeld model is physical across the whole range; the bare Spitzer model gives unphysical absorption of 80 - 100 % at low temperature (due to the high collision frequency), and the bare WDM model diverges at high temperature (no lattice). The Electron-Phonon model, with the ceiling and the Spitzer hand-off, is bounded and physical across all temperatures.

Because the absorption is a monotone function of the collision frequency through Eq. (40), and the low-temperature collision frequency carries an empirical coefficient— K_{wds} in the electron–phonon branch of Eq. (23), or equivalently the prefactor K_{ds} multiplying the argument of the Drude–Sommerfeld logarithm in Eq. (27)—the analytic absorption inherits a controlled dependence on that coefficient. Varying it and propagating the result through the Fresnel relation **maps how strongly the absorbed fraction responds to the variations of empirical coefficients**. Figure 6 shows the analytic absorption computed with different coefficients. A larger coefficient raises the collision frequency, moves the plasma deeper into the $\nu \sim \omega$ regime, and increases the absorbed fraction. The sensitivity is strongest in the low-temperature, near-solid regime where the electron–phonon branch dominates, and lower at high temperature.




Figure 6: (a) Analytic absorption for the Drude–Sommerfeld, Spitzer, WDM, and Electron-Phonon models. The absorption maximum near $T_e \sim 10 \text{ eV}$ (where $\nu \sim \omega$) tests the collision-frequency ceiling and the ionization chain. (b) Analytic absorption as a function of the collision-model coefficient.

Figure 7 compares the analytic models with the *HELIOS-CR* results. The absorption is evaluated at the plasma boundary as the difference between the incident laser power and

the power remaining after the wave solver has accumulated the absorption across all cells. The excellent agreement with the analytic solution verifies the correct implementation of the wave solver.




Figure 7: Simulations output (markers) against the self-consistent analytic absorption (lines) for the Drude–Sommerfeld, Spitzer, and Electron-Phonon models. The absorption maximum near $T_e \sim 10$ eV (where $\nu \sim \omega$) tests the collision-frequency ceiling and the ionization chain.

Remark on the Coulomb logarithm. The Coulomb logarithm in *HELIOS-CR* is evaluated with a choice of cutoffs and a low-temperature floor that differ from the analytic prescription used in the MULTI-fs implementation (Ramis *et al.* 2012, Eq. 53), which is

$$\ln \Lambda = \frac{1}{2} \ln \left(1 + \frac{\lambda_D^2}{b_{\min}^2} \right), \quad \lambda_D = \sqrt{\frac{k_B T_e}{4\pi n_e e^2}}, \quad b_{\min} = \max \left(\frac{\bar{Z} e^2}{m_e v_{th}^2}, \frac{\hbar}{m_e v_{th}} \right), \quad (43)$$

i.e. the electron Debye length as the maximum impact parameter and the larger of the classical distance of closest approach and the de Broglie wavelength as the minimum, with a floor $\ln \Lambda \geq 2$. The *HELIOS-CR* logarithm follows the NRL formulary, uses a Debye maximum impact parameter, and applies a different cutoff floor $\ln \Lambda \geq 1$. Since $\nu_{Sp} \propto \ln \Lambda$, the difference in Coulomb logarithm conventions significantly affects the collision frequency below $T_e \approx 300$ eV, as shown in Figure 4.

To remain consistent with the MULTI-fs implementation, the MULTI-fs logarithm is always used in the wave-solver laser-deposition model together with the electron–phonon collision model, while the *HELIOS-CR* logarithm is used in all other calculations. The Spitzer model is not offered as an option for the laser-deposition model: it gives nonphysical results at low temperature and is recovered as the high-temperature limit of the electron–phonon model.

5.2 Laser absorption for different polarization

Following the MULTI-fs notation, the solution of the Maxwell equations is implemented for both s- and p-polarization, and the laser can be injected at any incidence angle between 0 and 89 degrees. To verify this implementation, the following comparison with the analytical solution is performed.

At oblique incidence, the two polarizations diverge, following the Fresnel step-interface relations.

$$R_s = \left| \frac{\cos \theta - \hat{N}_\theta}{\cos \theta + \hat{N}_\theta} \right|^2, \quad R_p = \left| \frac{\hat{\varepsilon} \cos \theta - \hat{N}_\theta}{\hat{\varepsilon} \cos \theta + \hat{N}_\theta} \right|^2, \quad \hat{N}_\theta = \sqrt{\hat{\varepsilon} - \sin^2 \theta}. \quad (44)$$

The p-polarization reflectivity dips to a shallow pseudo-Brewster minimum (never reaching zero, since the metal is absorbing) while the s-polarization rises monotonically toward grazing incidence (Fig. 8).




Figure 8: Reflectivity versus incidence angle θ at 800nm and fixed $T_e = 30$ eV for s- and p-polarization: analytic Fresnel curves (lines) and simulation output (markers). The p-polarization pseudo-Brewster dip is the most sensitive test of the oblique-incidence boundary conditions.

Comparison of the analytical solution with simulation results (obtained in the same way as in the previous section) is shown in Figure 8. The simulation results are in agreement with the analytical calculations, confirming the correct implementation of the models.

5.3 Deposition profile verification

To verify the laser deposition profile under the same conditions of constant density and temperature, an algorithm analogous to the one described in the MULTI-fs paper has been implemented in Python for validation purposes. The full-wave (fast-physics) deposition

model solves the stationary Maxwell equations by the transfer-matrix method of the MULTIFS formulation (Ramis *et al.* 2012, Eqs. 35–44). The field is described by two amplitudes U (the oscillatory electric field for s-polarization, magnetic for p) and V , which, within each uniform cell, propagate through the analytic transfer matrix

$$\begin{pmatrix} U_j \\ V_j \end{pmatrix} = \begin{pmatrix} \cos(\beta_j \delta r) & -\frac{i}{p_j} \sin(\beta_j \delta r) \\ -i p_j \sin(\beta_j \delta r) & \cos(\beta_j \delta r) \end{pmatrix} \begin{pmatrix} U_{j+1} \\ V_{j+1} \end{pmatrix}, \quad p = \sqrt{\hat{\epsilon} - \sin^2 \theta}, \quad \beta = \frac{\omega}{c} p, \quad (45)$$

for s-polarization, with $p = \sqrt{\hat{\epsilon} - \sin^2 \theta} / \hat{\epsilon}$ for p. The product of the per-cell matrices relates the fields at the two ends of the layer. Two boundary conditions close the system: at the front the incident amplitude C_+ is fixed by the laser intensity, and at the back “no light is incident from the right” sets $C_- = 0$.

The absorbed power is obtained from the energy flux carried by the field. The time-averaged Poynting flux along the propagation direction is

$$\phi(x) = \frac{c}{16\pi} (U V^* + V U^*) = \frac{c}{8\pi} \text{Re}(U V^*), \quad (46)$$

and in the discretized scheme, the flux and the resulting specific deposition are

$$\phi_j = \frac{c}{16\pi} (U_j V_j^* + V_j U_j^*), \quad \left(\frac{D_e}{\rho} \right)_j = \frac{\phi_j - \phi_{j+1}}{m_j}, \quad (47)$$

i.e. the deposited power in each cell is the divergence of the Poynting flux across it.

Figure 9 compares the analytic solution with the *HELIOS-CR* results for a plasma of size $1.4 \mu\text{m}$, with the inset showing a magnified view of the front region. The two profiles are in good agreement across the whole domain: the plasma is large enough that the laser is fully absorbed before reaching the outer boundary, so the condition of no incident power from the right is satisfied and the boundary condition is consistent between the code and the analytic model.

Figure 10 shows the same comparison for a plasma of size $0.14 \mu\text{m}$. Here the two profiles disagree near the outer edge, because the domain is too small for the laser to be fully absorbed: a finite field reaches the boundary, the assumption of no incident power from the right no longer holds, and the boundary condition is not satisfied.

Practical note. For accurate results, the simulation must be performed on a sufficiently large domain—one on which the laser power is fully absorbed before the outer boundary, so that no appreciable power or absorption remains there. When this condition is met, the analytic and code deposition profiles agree; when it is violated, as in Fig. 10, a discrepancy appears at the edge.

5.4 Laser absorption as a function of wavelength

The Drude–Sommerfeld dielectric function of Eq. (32) is a *free-electron* model: it represents the conduction electrons as a collisional plasma and contains no bound-electron (interband) response.




Figure 9: Deposition profile dP/dx versus depth for a uniform slab of size $1.4\text{ }\mu\text{m}$ ($n_e/n_c \simeq 102.8$, $T_e = 10\text{ eV}$, $\lambda = 800\text{ nm}$): the analytic transfer-matrix solution (solid) against the *HELIOS-CR* wave solver (dashed). The inset magnifies the front $0\text{ }\mu\text{m}$ to $0.3\text{ }\mu\text{m}$. The laser is fully absorbed within the domain, the outer-boundary condition is satisfied, and the two profiles agree.




Figure 10: Deposition profile for a smaller slab of size $0.14\text{ }\mu\text{m}$, otherwise identical to Fig. 9. The laser is not fully absorbed within the domain; a finite field reaches the outer boundary, the assumption of no incident power from the right is violated, and the analytic and code profiles disagree near the edge.

The cold-solid absorption $A = 1 - R$ predicted by the model is compared against the value computed from *measured* room-temperature optical constants $n + ik$ (Rakić *et al.* 1998; Johnson & Christy 1972 for copper), through the same Fresnel relation $A = 1 - |(1 - \hat{N})/(1 + \hat{N})|^2$ with $\hat{N} = n + ik$. The measured constants are the experimental benchmark; the agreement with the model then measures how well the free-electron picture holds.

Table 1: Cold-solid absorption $A = 1 - R$ from measured optical constants (Rakić 1998; Johnson & Christy 1972), at the four validation wavelengths. Aluminium is nearly wavelength-flat and free-electron-like; copper shows the interband edge near 590 nm (absorption collapses in the infrared); titanium is strongly absorbing at all wavelengths through its d -band response.

Material	400 nm	527 nm	800 nm	1064 nm
Aluminium	7.6%	8.3%	13.2%	5.1%
Copper	49.0%	38.9%	3.6%	2.2%

Table 1 and Fig. 11 establish the domain of validity of the free-electron model:

- **Aluminium** is a nearly ideal free-electron metal (three conduction electrons, no low-lying d band). The measured absorption is lower compared to the analytical solution, probably due to a significantly higher collisional frequency compared to the experimental values ($\nu_{\text{Al}} \simeq 8.5 \times 10^{14} \text{ s}^{-1}$ EP model gives better results if the Kwdm is adjusted).
- **Copper** is free-electron-like only in the infrared. Its interband absorption edge near 590 nm (the transition responsible for copper’s colour) lifts the measured absorption to $\sim 40\text{--}50\%$ in the visible, which the free-electron model cannot reproduce. In the infrared (800 nm, 1064 nm), below the edge, the free-electron description is again reasonable, and the measured absorption is low. The Drude–Sommerfeld model is therefore usable for copper *only for* $\lambda \gtrsim 800 \text{ nm}$.

5.5 Laser absorption comparison with experiment

The ultimate test of the laser deposition model is a direct comparison against measured absorption. To validate its implementation in the *HELIOS-CR* hydrodynamic calculations, we compare against the experimental measurements reported in Price *et al.* (1995) for aluminium at 400 nm. As in the paper, the absorption is taken at the peak of the laser intensity, which is initialized with a Gaussian shape and a duration of $3 \times 10^{-13} \text{ s}$. This confirms both the laser deposition model and its effect on the plasma dynamics, characterized by the maximum plasma temperature reached at the peak of the laser pulse.

Figure 13 compares the simulated femtosecond absorption against the Price *et al.* (1995) data. The absorption rises with intensity as the surface heats and ν evolves, reaches a maximum, and rolls over at the highest intensities, where the collisional description gives way to kinetic absorption ($I\lambda_{\mu\text{m}}^2 \gtrsim 10^{17}$). A secondary axis maps intensity to the peak surface temperature, so the temperature regimes identified above can be read directly off the experimental curve. The Drude–Sommerfeld model reproduces the shape of the experimental




Figure 11: Cold-solid absorption versus wavelength for the three materials: the free-electron Drude–Sommerfeld model (curves) against the absorption computed from measured optical constants (markers, Table 1). Agreement is good for aluminium at all wavelengths, for copper only in the infrared (the model misses the visible interband edge), and




Figure 12: Illustration of how we can adjust K_{wdm} coefficients to match the experimental numbers

data with good quantitative accuracy above 30 eV, while below this temperature it overestimates the absorption. The Electron-Phonon model is highly sensitive to the combination of numerical constants for the electrical resistivity (the strongest dependence), the plasma conductivity, and the electron-ion heat exchange.




Figure 13: Absorption versus intensity for aluminium at 400 nm: simulation (Drude–Sommerfeld and full model) against the Price *et al.* (1995) measurement. The upper axis maps intensity to peak surface temperature; the shaded bands mark the degenerate, warm-dense-matter, and Spitzer regimes.

Figure 14 shows the maximum plasma temperature against the laser intensity. The experimental results in reasonable agreement with the Drude–Sommerfeld simulation.

5.6 Benchmark for an Integrated Simulation

Finally, an integrated simulation for a laser-driven foil was performed with *HELIOS-CR*. The evolution of the electron temperature and mass density distributions was compared against MULTI-fs results (Figures 4 and 5 of [6]). Figure 15 illustrates the simulation results for an aluminum foil irradiated by a 150 fs, 10^{15} W/cm² 400-nm laser pulse with a sinusoidal time profile. The simulations are in good quantitative agreement. Some differences in the results are expected because the numerical implementation and the use of EOS tables may differ substantially between *HELIOS-CR* and MULTI-fs.




Figure 14: Maximum electron temperature versus intensity for aluminium at 400 nm: simulation (Drude-Sommerfeld and full model) against the Price *et al.* (1995) measurement.




Figure 15: Final electron temperature and mass density profiles for *HELIOS-CR* (color plots) and *MULTI-fs* (black and white, from [6]) for an aluminum foil irradiated by a 150 fs, 10^{15} W/cm² 400-nm laser pulse.

6 Supplementary Materials




Figure 16: Conductivity benchmark for Section 3: Temperature-dependent conductivities for Al with $\rho=0.215$ g/cc computed with different models.

Heat front propagation in initially cold plasma slab for different values of flux-limiter. is applied to the left boundary of the slab.

Additional benchmark calculations for Section 5. Comparisons between *HELIOS-CR*, MULTI-fs, and the analytic solution at room temperature are shown in Figure 26 at 1 g/cc density, and Figure 27 near the critical density of 0.25 g/cc. As density is lowered, the oscillatory part of the solution becomes significant. In this case, widening the plasma shows that the laser power still attenuates. Laser deposition for a 0.1 g/cc plasma is shown in Figure 28 for (a) a $0.15\text{-}\mu\text{m}$ plasma, and (b) a $15\text{-}\mu\text{m}$ plasma, where the zoom inset shows the oscillations still present in the decay. This shows that such oscillatory behavior is indeed part of the solution to the differential equations. Similar agreement is seen at 1000 eV temperature in Figure 29(a) at 0.1 g/cc density, and Figure 29(b) at the lower density of 0.01 g/cc. The 5% difference in some MULTI-fs plots can be explained by differences in the physical constants used in that code. In order to minimize such differences, as well as differences due to EOS tables, the electron density was hard-wired to those used in the *HELIOS-CR* calculation.




Figure 17: Same as Figure 16 for H with $\rho=1 \text{ g/cc}$.




Figure 18: Same as Figure 16 for C with $\rho=1 \text{ g/cc}$.




Figure 19: Benchmarks for Section 3. Analytic solutions for temperature front propagation. Constant density, specific heat, and conductivity K . Instantaneous δ -function heat source. Analytic solution for planar geometry: $T \sim \frac{1}{(4\pi Kt)^{1/2}} \cdot e^{-x^2/(4Kt)}$.




Figure 20: Same as Figure 19. Analytic solution for spherical geometry: $T \sim \frac{1}{(4\pi Kt)^{3/2}} \cdot e^{-x^2/(4Kt)}$.




Figure 21: Same as Figure 19. Time dependence of peak temperature for planar and spherical geometries.




Figure 22: Same as Figure 20 for non-constant conductivity $K \sim T^{5/2}$. Analytic solution can be expressed in terms of Γ -functions and evaluated numerically.




Figure 23: Benchmarks for Section 3. Analytic solutions for temperature front propagation for plasma with constant density and specific heat. Conductivity $K \sim T^{5/2}$. Constant temperature source (hot dense slab) is applied to the left boundary of the slab. Self-similar solution exists, which can be solved with a 2nd order ODE. Helios solution matches the self-similar solution exactly (shown at 10 ps).




Figure 24: Benchmarks for Section 3. Heat front propagation in initially cold plasma slab for different values of flux-limiter. Constant temperature source (hot dense slab) is applied to the left boundary of the slab.




Figure 25: Same as Figure 24 for different flux-limiter options.




Figure 26: Deposition of a 500 TW/cm^2 , 400-nm laser compared between *HELIOS-CR*, MULTI-fs, and the analytic solution for constant plasma conditions for a room-temperature aluminum plasma at 1 g/cc density, using the Drude-Sommerfeld ν_e model.




Figure 27: Deposition of a 500 TW/cm^2 , 400-nm laser compared between *HELIOS-CR*, MULTI-fs, and the analytic solution for constant plasma conditions for a room-temperature aluminum plasma at 0.25 g/cc density, using the Drude-Sommerfeld ν_e model.




Figure 28: Deposition of a 500 TW/cm^2 , 400-nm laser compared between *HELIOS-CR*, MULTI-fs, and the analytic solution for constant plasma conditions for a room-temperature aluminum plasma at 0.1 g/cc density, using the Drude-Sommerfeld ν_e model, for plasma of width (a) $0.15 \text{ } \mu\text{m}$, and (b) $15 \text{ } \mu\text{m}$.




Figure 29: Deposition of a 500 TW/cm^2 , 400-nm laser compared between *HELIOS-CR*, MULTI-fs, and the analytic solution for constant plasma conditions for a 1000-eV aluminum plasma, using the Drude-Sommerfeld ν_e model, at (a) 0.1 g/cc density of width $0.15 \text{ } \mu\text{m}$, and (b) 0.01 g/cc density of width $150 \text{ } \mu\text{m}$.

Appendix 1: BIBLIOGRAPHY & REFERENCES CITED

- [1] J.J. MacFarlane, I.E. Golovkin, and P.R. Woodruff. HELIOS-CR – a 1-d radiation-magnetohydrodynamics code with inline atomic kinetics modeling. *Journal of Quantitative Spectroscopy and Radiative Transfer*, 99(1-3):381–397, May 2006.
- [2] Francis F. Chen. *Introduction to Plasma Physics and Controlled Fusion*. Springer International Publishing, 2016.
- [3] James J Duderstadt and Gregory A Moses. *Inertial Confinement Fusion*. John Wiley & Sons, Nashville, TN, March 1982.
- [4] Lyman Spitzer. *Physics of Fully Ionized Gases*. Interscience Publishers, New York, 2nd edition, 1962.
- [5] B. Fryxell, K. Olson, P. Ricker, F. X. Timmes, M. Zingale, D. Q. Lamb, P. MacNeice, R. Rosner, J. W. Truran, and H. Tufo. Flash: An adaptive mesh hydrodynamics code for modeling astrophysical thermonuclear flashes. *The Astrophysical Journal Supplement Series*, 131(1):273, nov 2000.
- [6] R. Ramis, K. Eidmann, J. Meyer ter Vehn, and S. Hüller. MULTI-fs – a computer code for laser-plasma interaction in the femtosecond regime. *Computer Physics Communications*, 183(3):637–655, March 2012.
- [7] Jon T. Larsen and Stephen M. Lane. Hyades—a plasma hydrodynamics code for dense plasma studies. *Journal of Quantitative Spectroscopy and Radiative Transfer*, 51(1):179–186, 1994. Special Issue Radiative Properties of Hot Dense Matter.
- [8] Stanley Skupsky. Energy loss of ions moving through high-density matter. *Phys. Rev. A*, 16:727–731, Aug 1977.
- [9] Thomas A. Mehlhorn. A finite material temperature model for ion energy deposition in ion-driven inertial confinement fusion targets. *Journal of Applied Physics*, 52(11):6522–6532, 11 1981.
- [10] J. D. Johnson. The sesame database. Los Alamos National Lab., NM (United States), 06 1994.
- [11] Y. T. Lee and R. M. More. An electron conductivity model for dense plasmas. *The Physics of Fluids*, 27(5):1273–1286, 05 1984.
- [12] Stefano Atzeni and Jürgen Meyer ter Vehn. *The Physics of Inertial Fusion*. Oxford University Press, June 2004.
- [13] R. Ramis, R. Schmalz, and J. Meyer-Ter-Vehn. MULTI — a computer code for one-dimensional multigroup radiation hydrodynamics. *Computer Physics Communications*, 49(3):475–505, June 1988.